

# FEATURES & ADVANTAGES

## Housing:

- Aluminum housing with ventilation grille
- Toughened glass for solar cell laminating

## LED Optics:

- A-class Bridgelux LED SMD 170 LM/W
- Acrylic lens, high transmittance
- Batwing lighting distribution (type II)



## Electrical & Control:

- Mono solar panel, high photoelectric conversion efficiency, long life time
- Car-grade lithium ion battery, high quality, safe & durable, with over charging and over discharging protection

**Mono Solar Cell**  
 Photoelectric efficiency up to **21%**  
**25** years life time  
 State-of-art laminating craft

**Li-ion Battery Pack**  
 No leakage  
 No explosion  
 High temperature resistance  
 Over **1,500** times cycles

- Photoelectric triggering switch threshold at 15 LUX
- Smart phone bluetooth control, max 15~20 meters effective control distance

Discharging Light on < **15 lux** < Charging Light off


**Bluetooth APP Control**  
 Compatible with *Android & IOS*  
 Light reading & Management  
 Remote trouble shooting  
 Time + Light + Power control

**Quality Assurance**

Solid **5** years warranty for the whole light

## Electrical & Control:

- High charging efficiency MPPT controller, 15%-18% higher than the market level.



- Flexible structure and smart connection, easy maintenance
- -25°C ~ +65°C working temperature
- Wind resistance Class 16 wind scale
- CCTV Camera is optional
- Group control is optional
- Pathway indicator is optional



## Technical Parameters:

Item No.	Watt	Solar	Battery	LEDs	Lumens	CCT	Charging Time	Discharging Time
GLU-2100C	100W	18V 120W	12V 84AH	120pcs Brigdelux	13000-15000lm	2700k-6500k	6-8 hrs	> 36 hrs
GLU-2120C	120W	18V 130W	12V 96AH	120pcs Brigdelux	15600-18000lm	2700k-6500k	6-8 hrs	> 36 hrs
GLU-2150C	150W	30V 150W	22.2V 57.2AH	180pcs Brigdelux	22500-25500lm	2700k-6500k	6-8 hrs	> 36 hrs
GLU-2200C	200W	30V 180W	22.2V 67.6AH	180pcs Brigdelux	30000-34000lm	2700k-6500k	6-8 hrs	> 36 hrs

## Mechanic & packing:

Item No.	Packing	Net Weight	Gross Weight	Installation Height	Poles Distance	Light Size	Packing Size	Parts Packing Size
GLU-2100C	1pc/2 cartons	25.5kg	30.5kg	9-11 meters	27-33 meters	1570x450x45 (mm)	1645x525x120 (mm)	405x235x380 (mm)
GLU-2120C	1pc/2 cartons	26.5kg	31.5kg	10-12 meters	30-36 meters	1670x450x45 (mm)	1740x525x120 (mm)	405x235x380 (mm)
GLU-2150C	1pc/2 cartons	29.5kg	34.5kg	11-13meters	35-45 meters	1750x550x45 (mm)	1835x625x120 (mm)	405x235x380 (mm)
GLU-2200C	1pc/2 cartons	33.5kg	38.5kg	12-14meters	40-50 meters	1940x550x45 (mm)	2120x625x120 (mm)	405x235x380 (mm)

## Applications:



- Street lighting, parking lot lighting, flood lighting, wall lighting, garden yard lighting etc



## Installation Instruction:

**Please press the switch button on the end of the light to initiate before installing**

- Standard pole bracket mount



- Slipfitter mount



## Bluetooth Control Setup & functions:

- 1) Install the App and make sure the location and bluetooth setup is open
- 2) Open the App, it will automatically search for light devices, connect and manage it

